

COPPER SEAM LUGS

Material : 99.9% copper, tin plated
 Operating Temperature : Up to 155°C
 Rating : Up to 30kV
 Compliance : AS/NZS 4325:1995, RoHS, REACH



*All dimensions in millimetres unless specified

Part Number	Screw Diameter (d2)	B	L	F	H	DØ	dØ
CSL8-5S	5.3	8.8	23.6	10.7	8.6	7.2	4.5
CSL8-5	5.3	15.0	29.6	13.8	8.6	7.2	4.5
CSL8-6	6.4	15.0	29.8	13.8	8.6	7.2	4.5
CSL8-8	8.4	15.0	29.8	13.8	8.6	7.2	4.5
CSL8-10	10.5	15.0	29.8	13.8	8.6	7.2	4.5
CSL8-12	13.0	22.0	39.5	20.8	8.6	7.2	4.5
CSL14-5	5.3	12.0	29.5	13.0	10.5	9.0	6.0
CSL14-6	6.4	12.0	29.5	13.0	10.5	9.0	6.0
CSL14-8	8.4	16.0	32.5	14.0	10.5	9.0	6.0
CSL14-10	10.5	16.0	32.5	14.0	10.5	9.0	6.0
CSL14-12	13.0	22.0	41.0	20.0	10.5	9.0	6.0
CSL22-6	6.4	12.2	32.7	14.5	12.3	11.7	8.0
CSL22-8	8.4	16.5	33.7	13.5	12.3	11.7	8.0
CSL22-10	10.5	16.5	33.7	13.5	12.3	11.7	8.0
CSL22-12	13.0	22.0	42.2	20.0	12.3	11.7	8.0
CSL38-8	8.4	15.3	39.0	17.2	14.1	13.1	9.2
CSL38-10	10.5	15.3	39.0	17.2	14.1	13.1	9.2
CSL38-12	13.0	22.0	42.7	17.7	14.1	13.1	9.2

