

NYLON P CLIPS

Material : Nylon 66
 Operating Temperature : -40°C to 85°C
 Flame Rating : 94V-2
 Features : Halogen free & Radiused interior edges
 Compliance : RoHS, UL



*All dimensions in millimetres unless specified

Part Number	A	B	C	D	E	F	Bundle Diameter
NP3.1SB	4.8	8.0	9.6	3.3	16.9	1.05	3.1 (1/8")
NP4.7SB	4.8	9.2	9.6	5.3	18.5	1.05	5.0 (3/16")
NP6.3SB	4.6	10.4	10.1	6.8	20.0	1.10	6.4 (1/4")
NP7.9SB	5.0	11.2	10.0	8.4	22.6	1.15	7.9 (5/16")
NP9.5SB	5.0	12.5	12.3	10.8	26.6	1.40	9.5 (3/8")
NP12.7B	5.0	14.8	12.2	13.8	30.3	1.40	12.7 (1/2")
NP15.8B	5.0	15.8	14.4	17.4	32.6	1.40	15.8 (5/8")
NP19B	4.8	18.0	11.8	19.9	37.3	1.40	19.4 (3/4")
NP25B	5.0	21.0	12.0	27.2	43.4	1.40	25.4 (1")
NP28.5B	4.8	26.0	12.6	30.6	51.5	1.70	27.5 (1 1/16")
NP31.8B	4.7	26.0	12.0	33.8	52.3	1.60	31.8(1 1/4")

