

HALOGEN FREE BOOT LACE PINS / FERRULES

Material : Copper tube
 Insulation: Nylon
 Tin plated finish

Operating Temperature : -40°C to 105°C

Voltage : 630V

Features : Halogen free
 Flame retardant

Compliance : RoHS, REACH, UL



**All dimensions in millimetres unless specified*

Part Number	Colour	F	L	D	C	Internal Cap Entry (W)	Wire Range (mm ²)	Max. Current Rating
BL034	Pink	6.0	10.5	1.1	0.8	2.5	0.34	-
BL034L	Pink	8.0	12.5	1.1	0.8	2.5	0.34	-
BL050	White	8.0	14.4	1.3	1.1	2.6	0.5	-
BL075	Blue	8.0	14.4	1.6	1.3	2.8	0.8	-
BL010	Red	8.0	14.4	1.8	1.5	3.0	1.0	-
BL010L	Red	12.0	18.4	1.8	1.5	3.0	1.0	-
BL015	Black	8.0	14.2	2.0	1.7	3.5	1.5	-
BL015L	Black	10.0	16.4	2.0	1.7	3.5	1.5	-
BL015XL	Black	18.0	24.4	2.0	1.7	3.5	1.5	-
BL025	Grey	8.0	15.6	2.6	2.3	4.0	2.5	-
BL025L	Grey	18.0	25.6	2.6	2.3	4.0	2.5	-
BL040	Orange	10.0	17.7	3.2	2.8	4.6	4.0	-
BL040L	Orange	12.0	19.7	3.2	2.8	4.6	4.0	-
BL040XL	Orange	18.0	25.7	3.2	2.8	4.6	4.0	-
BL040XXL	Orange	25.0	-	3.2	2.8	4.6	4.0	-
BL060	Green	12.0	20.0	3.9	3.5	6.0	6.0	-
BL060L	Green	18.0	26.0	3.9	3.5	6.0	6.0	-
BL060XL	Green	25.0	-	3.9	3.5	6.0	6.0	-

Part Number	Colour	F	L	D	C	Internal Cap Entry (W)	Wire Range (mm ²)	Max. Current Rating
BL100	Brown	12.0	21.2	4.9	4.5	7.4	10.0	-
BL100L	Brown	18.0	27.2	4.9	4.5	7.4	10.0	-
BL100XL	Brown	25.0	-	4.9	4.5	7.4	10.0	-
BL160	Ivory	12.0	22.2	6.2	5.8	8.5	16.0	-
BL160L	Ivory	18.0	28.2	6.2	5.8	8.5	16.0	-
BL160XL	Ivory	25.0	-	6.2	5.8	8.5	16.0	-
BL250	Black	16.0	27.8	7.9	7.5	11.0	25.0	-
BL250L	Black	22.0	34.0	7.9	7.5	11.0	25.0	-
BL250XL	Black	25.0	37.0	7.9	7.5	11.0	25.0	-
BL350	Red	16.0	30.0	8.7	8.3	12.7	35.0	-
BL350L	Red	25.0	39.0	8.7	8.3	12.7	35.0	-
BL500	Blue	25.0	41.0	10.9	10.3	15.3	50.0	-
BL700	Yellow	20.0	37.0	14.3	13.5	16.0	70.0	-
BL950	Red	25.0	43.6	15.3	14.5	18.2	95.0	-

