

## COPPER CABLE LINKS

Material	: Q195 steel & Electro-galvanised plating
Operating Temperature	: -55°C to 155°C
Total Conductivity	: 99.7% IACS
Total Resistivity	: 1.738 micro-ohm cm
Suitability	: AC applications
Rating	: 35kV
Material Grade	: ETP grade copper
Oxygen Content	: 30 ppm max
Tensile Strength	: 200 Mpa
Ductile Rating	: 40%
Other Metals	: Lead, antimony
Compliance	: AS/NZS 4325:1995, RoHS, REACH



*\*All dimensions in millimetres unless specified*

Part Number	Cable Size (mm <sup>2</sup> )	Barrel I.D. (A)	Barrel O.D. (C)	Total Length (L)
CTS1.5	1.5	1.8	3.7	22
CTS2.5	2.5	2.4	4	22
CTS4	4	3.1	4.8	22
CTS6	6	3.8	5.5	22
CTS10	10	4.7	7.1	22
CTS16	16	5.5	7.9	44
CTS25	25	7.1	9.5	47
CTS35	35	8.2	11.2	47
CTS50	50	9.5	12.8	47
CTS70	70	11.2	14.3	50
CTS95	95	13.5	17.4	54
CTS120	120	15.6	20.6	65
CTS150	150	16.7	22.5	65
CTS185	185	18.4	24.2	65
CTS240	240	21.2	28.2	90
CTS300	300	23.5	31.3	90
CTS400	400	26.8	34.8	90
CTS500	500	30	39	112
CTS630	630	34	45	112

