

## LONG PALM LUGS

Material : 99.9% copper, 99.9% tin plated  
 Operating Temperature : Up to 155°C  
 Rating : Up to 30kV  
 Compliance : AS/NZS 4325:1995, RoHS, REACH



\*All dimensions in millimetres unless specified

Part Number	Barrel Length (B)	Palm Width (D)	Palm Length (P)	Barrel O.D. (C)	Barrel I.D. (A)	Total Length (L)
CTLLP16-S	21	11	61	7.9	5.5	86
CTLLP16	21	16.5	61	7.9	5.5	86
CTLLP25	29	15	61	9.5	7.1	94.5
CTLLP35	35	16	72	11.2	8.20	112
CTLLP50	44	19	80	12.8	9.5	130
CTLLP70	48	21	100	14.3	11.2	154
CTLLP95	54	25	100	17.4	13.5	161
CTLLP120	60	29	100	20.6	15.6	168
CTLLP150	60	32	100	22.5	16.7	169
CTLLP185	64	35	100	24.2	18.4	174
CTLLP240	80	40	100	28.2	21.2	192
CTLLP300	90	45	105	31.3	23.5	208
CTLLP400	100	50	110	34.8	26.8	225
CTLLP500	105	56	110	39	30	230
CTLLP630	115	63	110	45	34	242

