



4 CORE RJ11 DATA MECHS

Body Material	: PC	Connector Type	: Insulation-piercing type wiring method
Surface Finish	: Gloss	Cable Diameter	: 0.4 - 0.6mm*
Dimensions	: 20 x 31.2 x 20mm	Durability	: 750 cycles
Temperature Range	: -25°C to +65°C	Compatible LAN Types	: N/A
Current Rating	: 1.5A	Protocols	: Supports POE power supply up to 30W
Contact Pin Material	: Tin-phosphorus bronze C5191	Compliance	:
Contact Resistance	: ≤ 200MΩ (milliohm)		
Insulation Resistance	: ≥ 500MΩ (milliohm)		

*Compatible with non-standard fine wires of ≥ 0.3mm



8 CORE RJ45 DATA MECHS

Body Material	: PC	Connector Type	: Insulation-piercing type wiring method
Surface Finish	: Gloss	Cable Diameter	: 0.4 - 0.6mm*
Dimensions	: 20 x 31.2 x 20mm	Durability	: 750 cycles
Temperature Range	: -25°C to +65°C	Compatible LAN Types	: CAT5E compatible with 100Mbps, CAT6 compatible with 100Mbps and 1Gbps
Current Rating	: 1.5A	Protocols	: Supports POE power supply up to 30W
Contact Pin Material	: Tin-phosphorus bronze C5191	Compliance	: IEC 11801-1 2017
Contact Resistance	: ≤ 200MΩ (milliohm)		
Insulation Resistance	: ≥ 500MΩ (milliohm)		

*Compatible with non-standard fine wires of ≥ 0.3mm



Elec present the following information in good faith and to the best of our current knowledge. In line with our commitment to continually improve our products, we reserve the right to change materials and specifications without notice. This data is provided on the condition that the user will make their own determination as to the product's suitability for their individual purpose, none of the following information is intended as a recommendation of product use. Elec is not responsible for damages resulting from the use or reliance upon the product or the related information in any event or of any nature.